



Electric Pallet Truck



Specification:-

<u>Item</u>	<u>Unit</u>	<u>CBD20</u>
<u>Capacity</u>	<u>Q(kg)</u>	<u>2000</u>
<u>Load Center</u>	<u>C(mm)</u>	<u>600</u>
<u>Wheel Distance</u>	<u>Y(mm)</u>	<u>1354</u>
<u>Driving Wheel</u>	<u>mm</u>	<u>Φ252×78</u>
<u>Balance Wheel</u>	<u>mm</u>	<u>Φ80×60</u>
<u>Balance Wheel Distance</u>	<u>mm</u>	<u>500</u>
<u>Front Wheel</u>	<u>mm</u>	<u>Φ80×70</u>
<u>Front Wheel Distance</u>	<u>mm</u>	<u>378/523</u>
<u>Fork Min Height</u>	<u>H13(mm)</u>	<u>85</u>
<u>Lifting Height</u>	<u>H3(mm)</u>	<u>115</u>
<u>Handle Height</u>	<u>H14(mm)</u>	<u>1280/1180</u>
<u>Overall Length</u>	<u>L1(mm)</u>	<u>1733</u>
<u>Chassis Height</u>	<u>L2(mm)</u>	<u>583</u>
<u>Overall width</u>	<u>b1(mm)</u>	<u>720</u>
<u>Fork Width</u>	<u>b5(mm)</u>	<u>540/685</u>
<u>Fork Size</u>	<u>s/e/l</u>	<u>1150×160×60</u>
<u>Distance With Ground</u>	<u>m2(mm)</u>	<u>25</u>
<u>Turning Radius</u>	<u>Wa(mm)</u>	<u>1545</u>
<u>Travel Speed</u>	<u>km/h</u>	<u>4/5(load/unload)</u>
<u>Lifting Speed</u>	<u>mm/s</u>	<u>27/35(load/unload)</u>
<u>Descent Speed</u>	<u>mm/s</u>	<u>42/37(load/unload)</u>
<u>Max.Gradient Performance</u>	<u>%</u>	<u>6</u>
<u>Motor Rating</u>	<u>kw</u>	<u>0.75</u>
<u>Lifting Motor Power</u>	<u>kw</u>	<u>0.8</u>
<u>Battery V/Ah</u>	<u>V/Ah</u>	<u>24/210</u>
<u>Battery Weight</u>	<u>kg</u>	<u>160</u>
<u>Type of Driving</u>	<u>—</u>	<u>Pedestrian/Stand</u>