

## Magnetic Lifter



### Specification

Rated lifting Capacity(Kg)	Max breakaway force (Kg)	Dimensions (mm)				N.W (kg)
		L	B	H	R	
100	300	90	63	68	145	3
400	1200	160	95	180	160	11
600	1800	220	115	125	230	20
1000	3000	260	145	145	280	40
1500	3750	310	145	145	280	48
2000	5000	340	160	165	410	60
3000	7500	420	185	185	510	90
4000	10500	480	200	200	510	120
5000	15000	580	300	300	650	400

The Magnetic Lifter can be in variety industries for the transportation and lifting of steel, engine parts, semi manufactured goods and moulds, due to its magnetic

### Features

The magnetic Lifter's highest pulling force is 3:5 times greater than rated lifting capability.

Light weight, range from 10-125Kgs.

Safe : No Electricity is needed to operate the magnetic lifter, one operated there is less than 1% residual magnetism.

The simple switch and safety button design allows for one handed operation.

Larger sizes available, output up to 6000Kgs.

## Hydraulic Hand Pallet Truck



### Specification

Item	Unit	SL-II-K 25
Capacity	(Kg)	2500
Min. Fork Height	(mm)	75
Max. Fork Length	(mm)	190
Max. Lifting Height	(mm)	≤ 110
Fork Outside Distance	(mm)	520/685
Fork Length	(mm)	915/1100/1220
Fork Size	(mm)	160x50
Load Roller Single Wheel	(mm)	ø74x93
Load Roller Tandem Wheel	(mm)	ø 74x70
Steering Wheel	(mm)	ø 180x50
Material of Wheel	(mm)	Nylon/Polyurethane/Rubber